

Reversible Module

Optical Breakout - 4 channels (multimode)

XVVRMOBO4M



● Fiber ——— (D) destination point



The Optical Breakout - 4 channels (multimode) Reversible Module fits in the Theatrixx 8-bay Frame.

The module can be inserted in the 8-Bay Frame in either direction, allowing the inputs/outputs to be positioned either at the front or the back of the unit depending on the application. It is a fully passive module requiring no external power, and allows combining 4 optical signals into a single cable, allowing trunking applications. Video, network, audio and more can all be combined in a single cable!

Specifications

Supported Signals

| | |
|----------------------|---------------------|
| Multi-Core Connector | 1 x OpticalCON Quad |
| Single Connectors | 4 x ST |

Physical Specifications

| | |
|--------|--------------------|
| Height | 121.5 mm (4.78 in) |
| Depth | 225 mm (8.85 in) |
| Width | 41 mm (1.61 in) |
| Weight | 710 g (1.56 lbs) |

Environmental Specifications

| | |
|-----------------------|--------------------------|
| Relative Humidity | 0% to 90% non-condensing |
| Operating Temperature | 0-40 °C |

Power Requirements

| | |
|-------------------|----------------|
| Power Consumption | None (Passive) |
| Voltage Range | None (Passive) |

In the Box

Theatrixx Reversible Module Optical Breakout - 4 channels (multimode)

Certifications & Compliance

This device complies with the following international standards



Ordering Information

| | |
|------------|---|
| XVVRMOBO4M | Theatrixx Reversible Module Optical Breakout - 4 channels (multimode) |
| XVVRF8 | Theatrixx 8-Bay Frame |
| XVVRMBLANK | Theatrixx Blank Module |